



Total Piping Solutions, Inc.  
 1760 Haskell Rd  
 Olean, NY 14760  
 TEL: 716-372-0160

**TRIPL**

**SS TRIPLE TAP® 6.55-7.42 X**

**ABANDONED CORP**

**TORQUES (FT-LBS):**

**WORKING PRESSURES**

**BRANCH: 250 PSI**

**CIRCUMFERENTIAL: 175 PSI**

**MAX TEMP: 180°F / HDPE 85°F**

**STEEL, DI, CI,**

**HDPE DR 9, 11, &**

**HDPE DR 17: 60**

**PVC SDR 21 to 26**

**PVC DR 18 to 14:**

**ACSF07420300**

**MADE IN THE USA**

<u>SIZE</u>	<u>RANGE</u>
4" US	4.45-5.13
4" OS	4.74-5.61
6" US	6.55-7.42
6" OS	6.84-7.65
8" US	8.54-9.44
8" OS	8.98-9.84
10" US	10.64-11.46
10" OS	11.34-12.16
12" US	12.62-13.56
12" OS	13.65-14.42
14" US	15.22-16.16
14" OS	16.18-16.92
16" US	17.25-18.18
16" OS	18.42-19.23

**3" AND 4" DOMED  
 OUTLETS TO COVER  
 ANY CORP STOP  
 PIPE DIAMETERS  
 FROM 4" TO 16"**



**BOLT TORQUE SEQUENCE**

TPS  
 Total Piping Solutions, Inc.  
 1760 Haskell Rd  
 Olean, NY 14760  
 TEL: 716-372-0160

**TRIPLE TAP®**

SS TRIPLE TAP® 6.55-7.42 X 3"

**ABANDONED CORP**

**TORQUES (FT-LBS):**  
 STEEL, DI, CI, & AC: 85-125  
 HDPE DR 9, 11, & 13.5: 80  
 HDPE DR 17: 60  
 PVC SDR 21 to 26: 60  
 PVC DR 18 to 14: 85-125

**WORKING PRESSURES**  
 BRANCH: 250 PSI  
 CIRCUMFERENTIAL: 175 PSI

**MAX TEMP: 180°F / HDPE 85°F**

**ACSF0742030012**

**MADE IN THE USA**

816 0411 04.02.2011

**TOTAL  
 PIPING  
 SOLUTIONS**

**716-372-0160**

**SALES@TPS.US**

