

# GAS REPAIR PRODUCTS for Natural Gas Piping Systems

Split repair sleeves, weld-on repair and reinforcing sleeves, bell-joint and full-wrap repair clamps





### **Table of Contents**

| Defects/Repair Product Guidelines | Pages  | 2-4 |
|-----------------------------------|--------|-----|
|                                   | m agee |     |

### **Repair Clamps**

| Style 4 and 41 Collar Leak Clamps for Steel 2" - 12"      | 5 |
|---|---|
| Style 60 and 160 Bell Joint Clamps for Cast Iron 3" - 48" | 6 |
| Style 77 Band Clamps                                      | 7 |
| Style 118 Handiband Clamps 1/2" - 8"                      | 8 |
| Style 360 Clamps 2" - 24"                                 | 9 |

### **Repair Sleeves**

| Style 50 Split Repair & Tapping Sleeves                              | 10    |
|--|-------|
| Style 54 and 73 Split Repair Sleeves for Steel Pipe 2", 3", 4"       | 11    |
| Style 80 Readypack Sleeves for Cast Iron                             | 12    |
| Style 96 Innerpak Sleeves for High Pressure Steel - Expanded Body    | 13    |
| Style 126 "Bell-Pack' Split Repair Sleeve for CIP                    | .14   |
| Style 110 Reinforcing Sleeves for Welded Joints                      | 15-16 |
| Style 220 Reinforcing Sleeves - Encasement                           | 17-18 |
| Style 220-S Reinforcing Sleeves for Small Diameter Welds & Couplings | 18    |

**Dresser Pipeline Solutions** offers natural gas pipeline industry customers an array of high-pressure repair products and solutions, including clamps, split sleeves and weld-on reinforceing sleeves for pipeline integrity. These ruggedly built products, made of high-quality materials, are indispensable parts of a Dresser pipeline solutions portfolio that has been distinguished by industry-leading innovation and performance excellence for more than 135 years.

Our gas pipeline repair fittings are used to repair the most challenging pipe repair problems, fix pinhole leaks, cracks, and splits in steel and cast iron mains.

Dresser network of field sales representatives can make sure you get the solution that meets your pipeline repair needs. They are complemented by inside customer care specialists who understand the features, capabilities, and application requirements of each Dresser product.

Dresser Utility Solutions reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Dresser sales representative for the most current information.

### **STEEL Pipeline Defects and Dresser Repair Product Options**



### A. Longitudinal Breaks up to 8" ORB. Circumferential Breaks

#### Size Product Maximum Pressure Style 54 Split Sleeve 2" - 4" 500 psi Style 73 Split Sleeve 2" 500 psi Style 96 Split Sleeve 6" - 24" 500 psi 2" - 12" Style 360 Clamp See Chart, Page 9 14"- 24"



D. Small Pinhole Leaks, Splits and Corrosion Cracks or

E. Broken Weld

| Product                               | Size                  | Maximum Pressure   |
|---------------------------------------|-----------------------|--------------------|
| Style 54 Split Sleeve                 | 2" - 4"               | 500 psi            |
| Style 73 Split Sleeve                 | 2"                    | 500 psi            |
| Style 77 Band Clamp                   | 2" - 24"              | 150 psi            |
| Style 118 Handiband<br>Clamp (D only) | 1/2" - 4"<br>6" - 8"  | 150 psi<br>100 psi |
| Style 360 Clamp<br>(D only)           | 2" - 12"<br>14" - 24" | See Chart, Page 9  |



#### Leaking Collars

| Product               | Size     | Maximum Pressure |
|-----------------------|----------|------------------|
| Style 4 Collar Clamp  | 2" - 4"  | 1000 psi         |
| Style 41 Collar Clamp | 6" -12"  | 1000 psi         |
| Style 54 Split Sleeve | 2" - 4"  | 500 psi          |
| Style 73 Split Sleeve | 2"       | 500 psi          |
| Style 96 Split Sleeve | 6" - 24" | 500 psi          |



#### Leaking Coupled Joints

| Product               | Size     | Maximum Pressure                    |
|-----------------------|----------|-------------------------------------|
| Style 54 Split Sleeve | 2" - 4"  | See Chart, Page 9                   |
| Style 96 Split Sleeve | 6" - 24" | 500 psi                             |
| Style 220 Weld Sleeve | 2" - 26" | 400 - 1600 psi<br>See chart page 18 |

## **CIP/DIP Pipeline Defects and Dresser Repair Product Options**



### Longitudinal Breaks up to 8"

| Product               | Size                | Maximum Pressure  |
|-----------------------|---------------------|-------------------|
| Style 50 Split Sleeve | 4" and<br>above     | 100 psi           |
| Style 80 Split Sleeve | 4" - 8"             | 150 psi           |
| Style 360 Clamp       | 3" - 8"<br>10"- 24" | See Chart, Page 9 |



### Longitudinal Breaks from 8" - 16"

| Product          | Size                | Maximum Pressure  |
|------------------|---------------------|-------------------|
| Style 50 Special | 4" and above        | 100 psi           |
| Style 360 Clamp  | 3" - 8"<br>10"- 24" | See Chart, Page 9 |



#### **Circumferential Breaks**

| Product               | Size                 | Maximum Pressure  |
|-----------------------|----------------------|-------------------|
| Style 50 Split Sleeve | 4" and<br>above      | 100 psi           |
| Style 80 Split Sleeve | 4" - 8"              | 150 psi           |
| Style 360 Clamp       | 3" - 8"<br>10" - 24" | See Chart, Page 9 |



### Small Pinhole or Corrosion Leaks

| Product               | Size                 | Maximum Pressure  |
|-----------------------|----------------------|-------------------|
| Style 50 Split Sleeve | 4" and above         | 100 psi           |
| Style 80 Split Sleeve | 4" - 8"              | 150 psi           |
| Style 360 Clamp       | 3" - 8"<br>10" - 24" | See Chart, Page 9 |

### **CIP/DIP Pipeline Defects and Dresser Repair Product Options**



#### Cracked or Leaking Bell

| Product                                 | Size                 | Maximum Pressure |
|---|----------------------|------------------|
| Leaking Bell:<br>Style 60 Bell Clamp    | 3" - 24"             | 100 psi          |
| Style 160 Bell Clamp                    | 4" - 8"<br>12" & 16" | 100 psi          |
| Cracked Bell:<br>Style 126 Split Sleeve | 3" - 24"             | 100 psi          |



#### Leaking Inner-Tite Joint

| Product                | Size         | Maximum Pressure |
|------------------------|--------------|------------------|
| Style 126 Split Sleeve | 8", 20", 24" | 100 psi          |
| Style 126 Special      | 3" - 24"     | 100 psi          |



#### Leaking Coupled Joints

| Product                | Size     | Maximum Pressure |
|------------------------|----------|------------------|
| Style 126 Split Sleeve | 3" - 24" | 100 psi          |

| P           | A Star | - June - |
|-------------|--------|----------|
|             |        |          |
| 2 Alexandre |        | H        |
|             |        | 5        |
| 2           | 10.0   | an in    |

#### Leaking Mechanical Joints

| Product                | Size     | Maximum Pressur |
|------------------------|----------|-----------------|
| Style 126 Split Sleeve | 3" - 24" | 100 psi         |

### **Optional Repair**

Remove defective length of pipe, insert new pipe and join with two Style 38, 40 or 700 couplings.





# Style 4 and 41 Collar Clamps

#### Stops all leaks through screw collars

Dresser Style 4 and 41 clamps quickly and inexpensively stop leaks through the threads of screw collars (threaded couplings). Repairs are permanent and normally made without interrupting service or dismantling the line.

Style 4 clamps consist of two malleable split follower rings with interlocking ends on each section, two resilient split gaskets, and bolts as required for pipe sizes up to 4".

Style 41 clamps consist of the same parts, except the split follower rings are steel and are connected by steel lock links.

| Material Specifications |                                   |  |  |
|-------------------------|-----------------------------------|--|--|
| Followers               | Style 4 Malleable, Style 41 Steel |  |  |
| Bolts & Nuts            | Alloy to AWWA C111/ANSI A21.11    |  |  |
| Gasket                  | Grade 27 BUNA-S                   |  |  |





#### Style 4 (Malleable) - Size Specifications for 2" - 4"

| Nominal               | Outside               | Collar Dimensions          |                          | Bolts Number Clamp Dimensions     |                            | Gasket                   | Approximate                   |                                 |
|-----------------------|-----------------------|----------------------------|--------------------------|-----------------------------------|----------------------------|--------------------------|-------------------------------|---------------------------------|
| Size<br>Steel<br>(ID) | Size<br>Steel<br>(ID) | Overall<br>Diameter<br>(A) | Overall<br>Length<br>(B) | Diameter &<br>Length<br>(C and D) | Overall<br>Diameter<br>(G) | Overall<br>Length<br>(H) | Section<br>Dimensions<br>(in) | Shipping<br>Weight Ea.<br>(Ibs) |
| 2                     | 2.375                 | 2.841                      | 3.625                    | 4 - 5/8 x 6-1/2                   | 6-5/16                     | 7                        | 9/32 x 5/8                    | 8                               |
| 3                     | 3.500                 | 4.014                      | 4.125                    | 4 - 5/8 x 7-1/2                   | 7-1/2                      | 8                        | 11/32 x 3/4                   | 9                               |
| 4                     | 4.500                 | 5.233                      | 4.625                    | 4 - 5/8 x 7-1/2                   | 8-1/2                      | 8                        | 23/64 x 3/4                   | 11                              |

#### Style 41 (Steel) - Size Specifications for 6" ID - 12" ID

| Nominal               | Quitaida         | Collar Dimensions          |                          | Bolts Number                    | Clamp Dimensions           |                          | Gasket                        | Approximate                     |
|-----------------------|------------------|----------------------------|--------------------------|---------------------------------|----------------------------|--------------------------|-------------------------------|---------------------------------|
| Size<br>Steel<br>(ID) | Diameter<br>(OD) | Overall<br>Diameter<br>(A) | Overall<br>Length<br>(B) | Diameter &<br>Length<br>(C & D) | Overall<br>Diameter<br>(G) | Overall<br>Length<br>(H) | Section<br>Dimensions<br>(in) | Shipping<br>Weight Ea.<br>(Ibs) |
| 6                     | 6.625            | 7.482                      | 5.125                    | 6 - 5/8 x 8-1/2                 | 10-3/4                     | 9-1/2                    | 7/16 x 3/4                    | 23                              |
| 8                     | 8.625            | 9.596                      | 6.125                    | 6 - 5/8 x 9-1/2                 | 12-7/8                     | 10-1/2                   | 1/2 x 3/4                     | 28                              |
| 10                    | 10.750           | 11.958                     | 6.625                    | 8 - 5/8 x 10-3/4                | 15-3/8                     | 11                       | 5/8 x 23/32                   | 44                              |
| 12                    | 12.750           | 13.958                     | 6.625                    | 8 - 5/8 x 10-3/4                | 17-3/8                     | 11                       | 5/8 x 23/32                   | 50                              |

# Style 60 and 160 Bell Joint Clamps

For repair of cast iron bell and spigot joints



Dresser bell joint clamps permanently stop or prevent leaks through the jointing materials of cast iron bell and spigot joints. Completely adjustable to provide a close fit on both the pipe bell and spigot, one standard clamp fits virtually all makes of pipe within a nominal size.

Style 60 and 160 clamps can be quickly installed with no interruption of service. A large, special rubber compound gasket shuts off the leak when compressed as the spigot ring is drawn up and, in turn, by bolts connected to the bell ring (anchored on the bell).

#### Style 60 Clamp

The spigot ring of the Style 60 clamp offers a wide range of adjustment made possible by the use of clips having fillers with the same cross section of the spigot ring. Serrated ends on the bell ring sections offer a simple and effective means of adjustment, providing a positive fit for varying outside bell diameters.



| Material Specifications |                                |  |  |
|-------------------------|--------------------------------|--|--|
| Rings                   | Cast Ductile Iron to ASTM A536 |  |  |
| Bolts and Nuts          | AWWA C111/A21.11               |  |  |
| Spigot Ring Bolts       | ASTM A-307                     |  |  |
| Clips                   | Ductile or Malleable Iron      |  |  |
| Gasket                  | Grade 27 BUNA-S                |  |  |

#### Style 160 Clamp

The Style 160 clamp features a hinged, wraparound spigot ring design. There are no clips and the spigot sections have serrated ends that bolt together.

#### Style 60 and 160 - Size Specifications for 3" - 16"

| Nominal<br>Size<br>(CIP) | Gasket<br>Thickness<br>x Length | Bolts<br>Number Diam.<br>x Length | Weight<br>Shipping Ea.<br>(Ibs) |
|--------------------------|---------------------------------|-----------------------------------|---------------------------------|
| 3                        | 1-1/8 x 1                       | 4 – 5/8 x 5                       | 13                              |
| 4 <sup>1</sup>           | 1-1/8 x 1                       | 4 – 5/8 x 5                       | 15                              |
| 61                       | 1-1/8 x 1                       | 6 – 5/8 x 5-1/2                   | 21                              |
| 8 <sup>1</sup>           | 1-1/8 x 1                       | 6 – 5/8 x 5-1/2                   | 24                              |
| 10                       | 1-1/8 x 1                       | 8 – 5/8 x 5-1/2                   | 35                              |
| 12 <sup>1</sup>          | 1-1/8 x 1                       | 9 – 5/8 x 5-1/2                   | 38                              |
| 14                       | 1-1/8 x 1                       | 9 – 5/8 x 6                       | 46                              |
| 16¹                      | 1-1/8 x 1                       | 9 – 5/8 x 6                       | 50                              |

#### Dimensions are in inches unless otherwise noted.

<sup>1</sup>NOTE: Style 160 Clamps may be furnished in these sizes.

#### Style 60 and 160 - Size Specifications for 18" - 48"

| Nominal<br>Size<br>(CIP) | Gasket<br>Thickness<br>x Length | Bolts<br>Number Diam.<br>x Length | Weight<br>Shipping Ea.<br>(Ibs) |
|--------------------------|---------------------------------|-----------------------------------|---------------------------------|
| 18                       | 1-1/8 x 1                       | 12 – 5/8 x 6-1/2                  | 73                              |
| 20                       | 1-1/8 x 1                       | 12 – 5/8 x 6-1/2                  | 74                              |
| 24                       | 1-1/8 x 1                       | 12 – 5/8 x 7                      | 86                              |
| 30                       | 1-1/8 x 1                       | 16 – 5/8 x 7                      | 113                             |
| 36                       | 1-1/8 x 1                       | 20 – 5/8 x 7                      | 148                             |
| 42                       | 1-1/8 x 1                       | 24 – 5/8 x 7-1/2                  | 199                             |
| 48                       | 1-1/8 x 1                       | 24 – 5/8 x 7-1/2                  | 227                             |

### **Style 77 Band Clamps**

For repair of pinhole leaks



Dresser Style 77 band clamps are specifically designed to provide a low cost repair for small pinholes, leaks, corroded areas and pits in straight runs of steel piping. They are suitable for virtually all working temperatures and line contents. 150 MAOP in all sizes.

Each clamp consists of a flexible, one-piece carbon steel circular band that is sprung apart to fit over the pipe, and a high-strength carbon steel bolt and nut of sufficient diameter to provide both a safety factor and protection against corrosion. The 77 clamp is available in standard steel pipe sizes from 2" through 24" with 2" or 3" wide bands. NOTE: Cone gaskets are ordered separately and must be specified when ordering the Style 77 repair clamp with three different size cone gaskets available as noted below.

|             | Material Specifications                                       |
|-------------|---|
| Band/Lugs   | AISI C1008/1010 Carbon Steel                                  |
| Bolt & Nut  | AWWA C111/A21.11  |
| Gasket (77) | 100% Pure Gum Rubber; 1/4" Minimum<br>Thickness, 40 Durometer |

PRESSURE RATING: 150 PSI All Sizes

| Style 77         | Cone Gasket         | Order Separately       |
|------------------|---------------------|------------------------|
| Gasket<br>Number | Gasket Size<br>(in) | Dresser<br>Part Number |
| 216              | 1-5/8"              | 30770001001            |
| 217              | 2"                  | 30770002001            |
| 218              | 2-1/2"              | 30770004001            |

#### Style 77 Band Clamps - Size Specifications 2" - 24"

| Pipe (Steel)<br>Nominal<br>Size (ID) | Outside<br>Diameter<br>(OD) | Band<br>Thickness &<br>Width | Bolt<br>Diameter &<br>Length | Approximate Ship<br>Weight Ea. (lbs.) |
|--------------------------------------|-----------------------------|------------------------------|------------------------------|---------------------------------------|
| 2                                    | 2.375                       | 1/16 x 2                     | 1/2 x 4                      | 0.84                                  |
| 3                                    | 3.500                       | 1/16 x 2                     | 1/2 x 4                      | 0.96                                  |
| 4                                    | 4.500                       | 1/16 x 2                     | 1/2 x 5-1/2                  | 1.3                                   |
| 5                                    | 5.563                       | 1/16 x 2                     | 1/2 x 5-1/2                  | 1.4                                   |
| 6                                    | 6.625                       | 3/32 x 3                     | 5/8 x 6                      | 2.8                                   |
| 6-5/8 CAS                            | 7.000                       | 3/32 x 3                     | 5/8 x 6                      | 2.9                                   |
| 8                                    | 8.625                       | 3/32 x 3                     | 5/8 x 6                      | 3.4                                   |
| 10                                   | 10.750                      | 3/32 x 3                     | 5/8 x 7                      | 4.0                                   |
| 11-5/8 CAS                           | 12.000                      | 3/32 x 3                     | 5/8 x 7                      | 4.3                                   |
| 12                                   | 12.750                      | 3/32 x 3                     | 5/8 x 7                      | 4.5                                   |
| 14                                   | 14.000                      | 1/8 x 3                      | 5/8 x 8-1/4                  | 6.2                                   |
| 16                                   | 16.000                      | 1/8 x 3                      | 5/8 x 8-1/4                  | 6.9                                   |
| 18                                   | 18.000                      | 1/8 x 3                      | 5/8 x 8-1/4                  | 7.5                                   |
| 20                                   | 20.000                      | 1/8 x 3                      | 5/8 x 8-1/4                  | 8.2                                   |
| 24                                   | 24.000                      | 1/8 x 3                      | 5/8 x 8-1/4                  | 9.6                                   |

# **Style 118 Handiband Clamps**

#### For quick, permanent repair of small holes in steel pipe

The Dresser Style 118 Handiband Clamp is a field-proven, low cost band-type repair clamp for quick repair of small leaks and holes in steel gas piping. Installation is fast and easy. Simply wrap the clamp around the pipe with gasket centered over the leaking area, drop the boltheads through the slotted lugs and tighten the nuts. Compression of the large size gasket seals the leak completely and permanently. Note: Style 118's do not create a 360-degree seal around the pipe.

Individual components of the Style 118 clamp are carefully engineered and constructed with lugs of ductile iron and bolts plated for long life and durability. The Style 118 clamp is made of stainless steel for corrosion resistance in lengths of 3, 6 and 12". The rubber compounded gasket offers resistance to oil, aromatic and aliphatic hydrocarbons, condensates, gasoline and natural gas. These gaskets retain their resilience for the life of the pipeline.

| Material Specifications |                                |  |  |  |
|-------------------------|--------------------------------|--|--|--|
| Band                    | Stainless Steel 18-8, Type 304 |  |  |  |
| Lugs                    | Ductile Iron ASTM 536          |  |  |  |
| Bolts & Nuts            | ASTM A307                      |  |  |  |
| Gaskets                 | Gridded to Dresser specs       |  |  |  |

| Pressure Ratings |         |  |  |  |  |
|------------------|---------|--|--|--|--|
| 1/2" thru 4"     | 150 psi |  |  |  |  |
| 5" thru 8"       | 100 psi |  |  |  |  |





| Torque Recommendations |             |  |  |  |  |
|------------------------|-------------|--|--|--|--|
| Clamp Size             | Max Torque  |  |  |  |  |
| 1/2" thru 1-1/2"       | 25 ft. lbs. |  |  |  |  |
| 2" thru 8"             | 35 ft. lbs. |  |  |  |  |

| Style 118 Handiband Repair Clamp - Size Specifications | for 1/2" thru 8"; Band Lengths Options of 3", 6" and 12 |
|--|---|
|--|---|

| Nominal<br>Size<br>(ID) | Outside<br>Diameter<br>(OD) | Overall<br>Length<br>(in) | Quantity<br>per<br>Package | Weight Ea.<br>(lbs) |   | Nominal<br>Size<br>(ID) | Outside<br>Diameter<br>(OD) | Overall<br>Length<br>(in) | Quantity<br>per<br>Package |  |
|-------------------------|-----------------------------|---------------------------|----------------------------|---------------------|---|-------------------------|-----------------------------|---------------------------|----------------------------|--|
| 1/2                     | .840                        | 3                         | 20                         | .50                 |   | 3                       | 3.500                       | 3                         | 6                          |  |
| 1/2                     | .840                        | 6                         | 10                         | 1.00                |   | 3                       | 3.500                       | 6                         | 4                          |  |
| 3/4                     | 1.050                       | 3                         | 16                         | .60                 |   | 3                       | 3.500                       | 12                        | 2                          |  |
| 3/4                     | 1.050                       | 6                         | 8                          | 1.10                |   | 3-1/2                   | 4.000                       | 3                         | 6                          |  |
| 1                       | 1.315                       | 3                         | 16                         | .60                 |   | 3-1/2                   | 4.000                       | 6                         | 4                          |  |
| 1                       | 1.315                       | 6                         | 8                          | 1.20                |   | 4                       | 4.500                       | 3                         | 6                          |  |
| 1-1/4                   | 1.660                       | 3                         | 12                         | .90                 |   | 4                       | 4.500                       | 6                         | 4                          |  |
| 1-1/4                   | 1.660                       | 6                         | 6                          | 1.70                |   | 4                       | 4.500                       | 12                        | 2                          |  |
| 1-1/2                   | 1.900                       | 3                         | 12                         | .90                 |   | 5                       | 5.563                       | 3                         | 6                          |  |
| 1-1/2                   | 1.900                       | 6                         | 6                          | 1.80                |   | 5                       | 5.563                       | 6                         | 4                          |  |
| 2                       | 2.375                       | 3                         | 8                          | 1.11                |   | 6                       | 6.625                       | 3                         | 6                          |  |
| 2                       | 2.375                       | 6                         | 4                          | 2.30                |   | 6                       | 6.625                       | 6                         | 4                          |  |
| 2                       | 2.375                       | 12                        | 2                          | 4.50                |   | 6                       | 6.625                       | 12                        | 1                          |  |
| 2-1/2                   | 2.875                       | 3                         | 8                          | 1.20                |   | 8                       | 8.625                       | 3                         | 6                          |  |
| 2-1/2                   | 2.875                       | 6                         | 2                          | 2.30                |   | 8                       | 8.625                       | 6                         | 4                          |  |
|                         |                             |                           |                            |                     | I | Q                       | 8 625                       | 12                        | 1                          |  |

Dimensions are in inches unless otherwise noted.

NOTE: All orders for unpackaged sizes and for broken carton quantities will be randomly packaged

# **Style 360 Repair Clamps**

#### For fast repair of leaks in cast/ductile and steel mains

The Dresser Style 360 repair clamp offers simplicity and ease of installation. Just wrap the clamp around the pipe, drop the bolts in place and tighten. It's that simple! Moreover, special one-inch long nuts allow the use of a standard deep socket wrench for complete tightening. In the popular 7.5 inch clamp width, there is also a third bolt, so the middle bolt and nut can be used to pretighten the clamp. Additionally, the smaller clamps feature a flexible band, which means less holding force is required while tightening.

With the Style 360 clamp, you can repair holes, breaks and splits in the pipeline...You can even use it where pipe ends are separated, or where ends are deflected up to 4 degrees or 1/8 inch. Clamp features include a tapered gasket with a gridded design, and the spanner is molded flush with the gasket to prevent "hang up." The Style 360 clamp has a stainless band, lugs of rugged ductile iron and bolts of corrosion-resistant Dresserloy.

#### Style 360 Repair Clamp - Size Specifications

| Range<br>of Fit<br>(OD)  | Clamp<br>Widths   | Max.<br>psi  | Range<br>of Fit<br>(OD)   | Clamp<br>Widths                      | Max.<br>psi   |
|--|---|--|---|--------------------------------------|---|
| 2.35 - 2.63<br>2.70 - 3.00<br>2.97 - 3.25  | 7-1/2, 12-1/2<br>0.024 Thick<br>Band                    | 125  | 11.04 - 11.44<br>11.34 - 11.74<br>11.75 - 12.15<br>12.00 -12.40   | 7-1/2, 12-1/2,<br>15                 | 95<br>85<br>85<br>85  |
| 3.46 - 3.70<br>3.73 - 4.00<br>3.96 - 4.25<br>4.45 - 4.86<br>4.74 - 5.14  | 7-1/2,<br>12-1/2, 15,<br>20                             | 125  | 12.62 - 13.02<br>13.10 - 13.50<br>13.40 - 13.80<br>13.70 - 14.10<br>14.00 - 14.40   | 20, 30<br>0.036" Thick<br>Band       | 75<br>75<br>65<br>65  |
| 4.95 - 5.35  | 0.024" Thick<br>Band                                    |  | <b>2 Band Sizes</b><br>14.38 - 15.13  |                                      | 105   |
| 5.22 - 5.62<br>5.95 - 6.35<br>6.56 - 6.96<br>6.84 - 7.24<br>7.05 - 7.45<br>7.95 - 8.35<br>8.54 - 8.94<br>8.99 - 9.39<br>9.27 - 9.67<br>9.68 - 10.08<br>9.70 - 10.10<br>10.64 - 11.04 | 7-1/2,<br>12-1/2, 15,<br>20, 30<br>0.024" Thick<br>Band | 125<br>125<br>125<br>125<br>125<br>125<br>125<br>125<br>125<br>115<br>11 | $\begin{array}{c} 15.07 - 15.82 \\ 15.92 - 16.67 \\ 16.56 - 17.31 \\ 17.15 - 17.90 \\ 17.82 - 18.57 \\ 18.46 - 19.21 \\ 19.23 - 19.98 \\ 19.90 - 20.65 \\ 20.70 - 21.45 \\ 21.52 - 22.27 \\ 22.12 - 22.87 \\ 22.90 - 23.65 \end{array}$ | 20, 30<br>0.048" Thick<br>Multi-Band | 100<br>90<br>85<br>80<br>75<br>70<br>65<br>60<br>55<br>50<br>50<br>45 |

Dimensions are in inches unless otherwise noted.

NOTE: On any given installation, the pressure capability of the clamps is influenced by the type and extent of the damage, service conditions, environmental conditions and installation workmanship.



### **Style 360 Clamp Features:**

- One-inch long nuts allow tightening with standard deep socket wrench.
- Drop-in bolts No need to remove bolts in the ditch. No loose parts to misplace.
- Multi-band clamp Features a multiband design in the 14" through 24" sizes. Clamp is packaged and shipped "in the flat," meaning the bands are not formed to the radius of the pipe. Reduces storage space and installation time, and has twice the adjustment range of the single-band clamp.

| Material Specifications |   |  |  |  |
|-------------------------|---|--|--|--|
| Band                    | AISI Type 304 Stainless Steel                     |  |  |  |
| Lugs                    | Ductile Iron                                      |  |  |  |
| Nuts                    | AWWA C111/A21.11                                  |  |  |  |
| Bolts                   | AWWA C111/A21.11                                  |  |  |  |
| Spanner                 | AISI Type 304 Stainless Steel                     |  |  |  |
| Gasket                  | Gridded Surface to Dresser<br>Specs, 55 Durometer |  |  |  |

# **Style 50 Split Repair Sleeves**

#### Dual purpose sleeve for emergency repair or hot tapping CIP

The versatile Dresser Style 50 split repair sleeve can provide a safe, efficient method of hot tapping cast iron pipe under pressure. It can also be ordered without the pipe branch and serve as an emergency repair sleeve, eliminating the necessity of stocking separate tapping and repair sleeves.

Style 50 sleeves can be furnished with any size threaded, flanged or plain-end tapping branch, custom-fabricated at the plant to meet any requirement. Each sleeve can accommodate several branch sizes, permitting further inventory reductions. Branches can be supplied with special taps for insertion of bagging equipment when low pressure tapping is performed.

#### **Style 50 Sleeve Features:**

- Fabricated from steel and insulated from main to meet DOT standards
- Factory-assembled to facilitate handling, storage and ease of installation
- Sleeve halves are match-marked to assure a proper fit
- No service interruptions during the installation procedure
- Deflection and line stresses absorbed when used as a repair device for complete breaks
- Time-proven sealing principle and furnished with Dresser gray epoxy coating as standard
- Sleeve can be pressure tested to ensure sealing performance prior to tapping

#### **Style 50 Custom Fabricated Sleeves**

Contact Dresser Inside Sales for your custom branch service outlet applications

#### **Hot Taps**

The Dresser Style 50 Sleeve is easily integrated with Intervention Technologies LS2 flange fittings to provide an efficient hot tap of cast iron pipe under pressure. Custom fabrication with branch service outlets can also be coupled with Dresser bolted couplings for all your PE connection requirements.





#### **Style 50 Split Repair Sleeve for Cast Iron Pipe** Size Specifications for 6" - 24"

| Nominal<br>Size <sup>1</sup><br>(CIP) | Outside<br>Diameter<br>(OD) | Length<br>Between End<br>Gaskets | MAOP<br>(psi) |
|---------------------------------------|-----------------------------|----------------------------------|---------------|
| 6                                     | 6.90                        | 11-1/2                           | 100           |
| 8                                     | 9.05                        | 12                               | 100           |
| 10                                    | 11.10                       | 17-1/4                           | 100           |
| 12                                    | 13.20                       | 18-1/4                           | 100           |
| 16                                    | 17.40                       | 21-3/4                           | 100           |
| 20                                    | 21.60                       | 24                               | 100           |
| 24                                    | 25.80                       | 29                               | 100           |

Dimensions are in inches unless otherwise noted. <sup>1</sup> Style 50 sleeves may be furnished in sizes up to 48"

#### **Material Specifications**

**Consult Factory per Application** 

#### Style 50 with Service Branch Outlet

Size Specifications for 6" - 24"

| Nom.<br>Size <sup>1</sup><br>(CIP) | Outside<br>Diameter<br>(OD) | Length<br>Between<br>End<br>Gaskets | Maximum<br>Branch<br>Size | Max<br>Operating<br>Pressure <sup>2</sup><br>(psi) |
|------------------------------------|-----------------------------|-------------------------------------|---------------------------|--|
| 6                                  | 6.90                        | 10-1/2                              | 4 IPS                     | 100  |
| 8                                  | 9.05                        | 12                                  | 12 6 IPS                  |  |
| 10                                 | 11.10                       | 17-1/4                              | 6 IPS                     | 100  |
| 12                                 | 13.20                       | 18-1/4                              | 8 IPS                     | 100  |
| 16                                 | 17.40                       | 21-3/4                              | 12 IPS                    | 100  |
| 20                                 | 21.60                       | 24                                  | 16 IPS                    | 100  |
| 24                                 | 25.80                       | 29                                  | 16 IPS                    | 100  |

Dimensions are in inches unless otherwise noted.

<sup>1</sup> Style 50 sleeves may be furnished in sizes up to 48" or larger.

<sup>2</sup>Other pressures available on request

### Style 54 and 73 Cast Split Sleeves

For repair of defective joints on 2", 3" and 4" steel pipe



Dresser Style 54 cast split sleeves are designed to completely enclose and repair defective screw collars, plain or butt bell and spigot joints and double-bell circumferential welded joints. Style 54 sleeves can also be used to repair holes and splits up to 8"on steel pipe without service interuptions, and are vented for installation under pressure.

Style 54 sleeves are of rugged construction to permit safe repairs on high-pressure gas and oil transmission pipelines up to 500 PSI. Each sleeve is air-tested with 60 psi air pressure and 1000 psi hydrostatic pressure before shipment. The sleeves are shipped factory-assembled, with the end parts packed inside the sleeve body with the installation instructions.

Style 73 cast repair sleeves are similar in construction and provide a fast, permanent repair on steel lines where moderate pressures are involved.



| Style 54 Sleeves - | Size Specifications | for Steel Pipe | (500 psi |
|--------------------|---------------------|----------------|----------|
|--------------------|---------------------|----------------|----------|

| Nom.<br>Size<br>Steel | Outside<br>Diam. | End Bolts<br>No/Diameter | Side Bolts<br>No/Diameter | Inside D<br>Diamete | imension<br>r / Length | Overall I<br>Diamete<br>( | Dimension<br>r / Length<br>in) | Vent<br>Size | Weight<br>Ea. |
|-----------------------|------------------|--------------------------|---------------------------|---------------------|------------------------|---------------------------|--------------------------------|--------------|---------------|
| (ID)                  | (OD)             | x Length                 | x Lengui                  | (A)                 | (B)                    | (C)                       | (D)                            | (IPS)        | (ibs)         |
| 2                     | 2.375            | 8 - 1/2 x 4              | 10 - 3/4 x 2-1/2          | 6-7/8               | 11                     | 11-3/4                    | 20-1/8                         | 1            | 75            |
| 3                     | 3.500            | 8 - 5/8 x 4              | 10 - 3/4 x 2-1/2          | 8                   | 11                     | 13                        | 20-1/8                         | 1-1/4        | 85            |
| 4                     | 4.500            | 8 - 5/8 x 4              | 12 - 3/4 x 3              | 10-1/2              | 14-1/4                 | 16-1/8                    | 25-1/2                         | 2            | 154           |

#### Style 73 Sleeve - Size Specifications for Steel Pipe (500 psi)

| Nom.<br>Size<br>Steel | Outside<br>Diam. | End Bolts<br>No/Diameter | Side Bolts<br>No/Diameter | Side Bolts<br>o/Diameter |     | Overall I<br>Diamete<br>( | Dimension<br>r / Length<br>in) | Vent Size<br>(IPS) | Weight<br>Ea. |
|-----------------------|------------------|--------------------------|---------------------------|--------------------------|-----|---------------------------|--------------------------------|--------------------|---------------|
| (ID)                  | (00)             | x Length                 | x Length                  | (A)                      | (B) | (C)                       | (D)                            |                    | (IDS)         |
| 2                     | 2.375            | 8 - 6/16 x 3-1/2         | 6 - 5/8 x 2-1/2           | 3-15/16                  | 7   | 8 -1/2                    | 16-1/2                         | 1                  | 47            |

### Style 80 Split "Ready-Pack" Sleeves

#### For repairs on cast iron pipe







Dresser Style 80 split "ready-pack" sleeves are used to enclose and permanently repair breaks, splits and holes in cast iron pipe. With vent sizes 1" thru 3", Style 80 sleeves can also be used as an efficient, low-cost tapping sleeve for branch service connections.

Style 80 sleeve bodies are cast from close-grained gray iron. Steel follower rings on each end are completely enclosed in the sleeve body. Carbon steel set screws are drawn up against the follower ring to compress the gasket, creating total circumferential sealing on the pipe. Side bolts, which are fully enclosed within the sleeve body to prevent corrosion, are tightened to compress side gaskets and provide a complete leakproof seal.

Style 80 sleeves are recommended for all customary pressures where pipe wall thickness is in conformity with specifications for standard cast iron pipe.

|                | Material Specifications                                   |
|----------------|---|
| Body           | Cast Iron   |
| Vent Plug      | Forged Steel to ASTM A105 or Cast to ASTM A126-42 Class A |
| Follower Rings | Cold-formed carbon steel                                  |
| Bolts & Nuts   | Alloy to AWWA C111/ANSI A21.11                            |
| Gaskets        | Grade 29 Spec 328   |



#### Style 80 Split Sleeves - Size Specifications for Cast Iron Pipe (All Sizes 150 MAOP)

| Nom.<br>Pipe<br>Size | Range<br>of Fit | End<br>Screws<br>Number<br>Diam. | Side<br>Bolts<br>Number<br>Dia. | End<br>Gasket<br>Section<br>Dimen. | Side<br>Gasket<br>Section<br>Dimen. | l<br>Din<br>Di<br>Le | Inside<br>nension <sup>1</sup><br>iam. (E)<br>ngth (F) | Ov<br>Dim<br>Dia<br>Len | verall<br>ension<br>m. (G)<br>gth (F) | Vent<br>Diam.<br>(in) | Weight<br>Ea.<br>(lbs) |
|----------------------|-----------------|----------------------------------|---------------------------------|------------------------------------|-------------------------------------|----------------------|--|-------------------------|---------------------------------------|-----------------------|------------------------|
| (CIP)                | (02)            | A & B                            | C & D                           | (in)                               | (in)                                | (E)                  | (F)  | (G)                     | (H)                                   |                       |                        |
| 3                    | 3.75-4.00       | 12- 3/8X1                        | 4-5/8 x 5-1/2                   | 5/8 x 3/4                          | 5/16 x 1/2                          | 4                    | 5-5/32   | 9-3/8                   | 7-15/16                               | 1-1/4 - 2             | 40                     |
| 4<br>4²              | 4.74-4.99       | 12- 3/8X1                        | 4-5/8 x 5-1/2<br>2-5/8 x 5-1/2  | 5/8 x 3/4                          | 5/16 x 1/2                          | 4                    | 6-5/32   | 9-3/8                   | 8-15/16<br>10-7/8                     | 1 - 3<br>2 - 3        | 45<br>55               |
| 6²                   | 6.84-7.09       | 16- 3/8X1                        | 4-5/8 x 6-1/2<br>2-5/8 x 5-1/2  | 5/8 x 3/4                          | 5/16 x 1/2                          | 4                    | 8-1/4  | 9-5/16                  | 11-7/8                                | 2 - 3                 | 70                     |
| 8 <sup>2</sup>       | 8.99-9.24       | 20- 3/8X1                        | 4 5/8 x 7-1/2<br>2 5/8 x 5-1/2  | 5/8 x 3/16                         | 5/16 x 1/2                          | 7                    | 10-13/32   | 12-1/2                  | 11-7/8                                | 2 - 3                 | 100                    |

Dimensions are in inches unless otherwise noted.

<sup>1</sup> Inside Dimension "E" as indicated in cross section drawing, is distance between inside of end gaskets. This length is equal to or

greater than found between calking spaces in foundry "splits" as shown in AGA Standards Specifications for Service Sleeves.

<sup>2</sup> Long Pattern Design. Consult factory for specification details. Style 80 long body sleeves have six side bolts.

### **Style 96 Split Repair Sleeves**

#### Expanded body split sleeve for repairs on steel pipe

Dresser Style 96 split repair sleeves offer an expanded body for repairing coupled or mechanical joints on high-pressure steel transmission piping systems from 500 up to 1500 PSI.

Style 96 sleeves are fabricated from high-quality carbon steel and come completely factory-assembled for quick installation. All sleeves are vented for installation under pressure without service interruptions.



| Pressu              | re Ratings                 | Material Specifications |  |  |  |  |  |
|---------------------|----------------------------|-------------------------|--|--|--|--|--|
| ANSI 150<br>Standar | 0 to 500 PSI<br>rd Designs | Body Halves             | Weldable steel suitable for the particular application to ASTM A36 or equivalent |  |  |  |  |
| Up to 1,500 P       | SI On Application          | Follower                | Carbon Steel AISI C1015  |  |  |  |  |
| See Specifica       | tion Chart Below           | Cap Screws              | Heat-treated Carbon Steel C1038  |  |  |  |  |
| Temperature         | -20° F to +150° F          | Bolts/Studs/Nuts        | Meet ASTM A193 Grade B7 /ASTM A 194 Grade 2h or SAE Grade 8                      |  |  |  |  |
| Ratings             | for all sizes              | Gaskets                 | Dresser Grade 29   |  |  |  |  |
|                     |                            | Coatings                | Provided RED-D as standard: ALCLAD <sup>™</sup> fusion-bonded epoxy optional     |  |  |  |  |
|                     | CAP<br>SCREW               | VENT                    | END<br>GASKET  |  |  |  |  |

| Style 96 Split Sleeves | - Dimension | Specifications | for Steel | Pipe Sizes | 6"-24" |
|------------------------|-------------|----------------|-----------|------------|--------|
|------------------------|-------------|----------------|-----------|------------|--------|

| Pipe         | Pipe (Steel) ANSI 150 to 500 PSI |         |        | PSI    | Α        | NSI 300 | to 1000 F | PSI    | ANSI 600 to 1500 PSI |        |        |        |          |               |
|--------------|----------------------------------|---------|--------|--------|----------|---------|-----------|--------|----------------------|--------|--------|--------|----------|---------------|
| Nom.         | Out-                             | Inside  | Dim.   | Overa  | all Dim. | Inside  | e Dim.    | Overa  | ll Dim.              | Inside | e Dim. | Overa  | III Dim. | Vent          |
| Size<br>(in) | side<br>Diam.<br>(OD)            | (A)     | (B)    | (C)    | (D)      | (A)     | (B)       | (C)    | (D)                  | (A)    | (B)    | (C)    | (D)      | Diam.<br>(in) |
| 6            | 6.625                            | 12-/5/8 | 14     | 17-7/8 | 18-3/8   | 12-5/8  | 13-3/4    | 19-5/8 | 22-3/4               | 12-5/8 | 15-1/4 | 20-5/8 | 25       | 2             |
| 8            | 8.625                            | 14-5/8  | 14     | 19-7/8 | 18-3/8   | 10-7/8  | 13-3/4    | 19-5/8 | 22-3/4               | 14-5/8 | 15-1/4 | 22-5/8 | 25       | 2             |
| 10           | 10.750                           | 16-3/4  | 14-1/4 | 22     | 18-7/8   | 14-5/8  | 16-3/8    | 24-1/4 | 26-7/8               | 16-3/4 | 16-3/8 | 25-1/8 | 27       | 3             |
| 12           | 12.750                           | 18-3/4  | 14-1/4 | 24-1/4 | 20-3/4   | 16-3/4  | 16-3/8    | 26-1/4 | 22-7/8               | 18-3/4 | 18     | 31     | 31-1/2   | 3             |
| 14           | 14                               | 20      | 14-1/4 | 25-1/2 | 20-3/4   | 18-3/4  | 16        | 29-1/2 | 28                   | 20     | 18     | 32     | 31-1/2   | 3             |
| 16           | 16                               | 20      | 14-1/4 | 27-1/2 | 20-3/4   | 20      | 18        | 32     | 29-1/2               | 22     | 18     | 34     | 31-1/2   | 4             |
| 18           | 18                               | 20      | 14-1/4 | 29-1/2 | 20-3/4   | 22      | 20-1/4    | 35-3/8 | 34                   | 24     | 18     | 36     | 31-1/2   | 4             |
| 20           | 20                               | 26      | 14-1/4 | 32-1/4 | 20-3/4   | 24      | 15-1/4    | 35     | 27                   | 26     | 18     | 38     | 31-1/2   | 4             |
| 22           | 22                               | 28      | 14-1/4 | 34-1/4 | 20-3/4   | 26      | 16-1/2    | 40-3/8 | 32                   | 28     | 18     | 38     | 31-1/2   | 4             |
| 24           | 24                               | 30      | 16     | 36-1/8 | 22-1/2   | 28      | 16-1/2    | 42     | 32                   | 29-5/8 | 18     | 42     | 35       | 4             |

### **Style 126 Bell-Pack Repair Sleeves**

#### For repair of broken cast iron bell and spigot joints

Pipeline maintenance personnel avoid pipeline shutdowns and expensive, temporary makeshift repairs by installing the Dresser Style 126 Bell-Pack repair sleeve for a fast, economical and permanent repair. A sleeve of lighter weight and compact design, the Style 126 provides maximum inside dimension clearance for repairing split cast iron bells and leaking mechanical joints.

Built to rigid Dresser specifications, Style 126 repair sleeves provide the time-proven features of the Dresser rubber-packed gasket sealing design. Side bolts enclosed within the sleeve body, are

then tightened to compress side gaskets providing a complete, permanent leakproof seal.





| CELLEL CONT |  |  |  |
|-------------|--|--|--|
|-------------|--|--|--|

| М          | aterial Specifications  |
|------------|---|
| Body       | Cast or malleable iron through 8"<br>CIP. Larger sizes are special designs<br>fabricated steel plate and bar. |
| Vent Plug  | Forged Steel to ASTM A105 or Cast to ASTM A126-42 Class A   |
| Followers  | Cold-formed carbon steel  |
| Bolts      | Alloy to AWWA C111/ANSI A21.11  |
| Gaskets    | Grade 29  |
| Set Screws | Carbon Steel, Cadmium Plated  |
| Coating    | Dresser RED-D shopcoat standard;<br>Fusion bonded epoxy optional  |

#### Style 126 Repair Sleeve - Specifications for Cast Iron Sizes 4"- 24" (100 PSI

| Nom.<br>Size | Outside<br>Diam. | End Screws <sup>1</sup><br>Number<br>Dia x Length | Short Side<br>Bolts<br>Number <sup>2</sup> | Long Side<br>Bolts<br>Number | Side Inside<br>ts Dimension<br>ber Diameter Length |        | O<br>Dim<br>Diamet | verall<br>ension<br>ter Length | Vent <sup>3</sup><br>Diam. | Weight<br>Approx.<br>Ea. |
|--------------|------------------|---|--|------------------------------|--|--------|--------------------|--------------------------------|----------------------------|--------------------------|
| (CIP)        | (OD)             | (A) & (B)   | Dia. x<br>Length                           | Dia. x<br>Length             | (E)  | (F)    | (G)                | (H)                            | (in)                       | (lbs)                    |
| 4            | 4.800            | 12–3/8 x 1  | 6–5/8 x 4                                  | 4–5/8 x 6                    | 10   | 12     | 14-1/2             | 19-1/16                        | 1                          | 136                      |
| 4            | 5.000            | 12–3/8 x 1  | 6–5/8 x 4                                  | 4–5/8 x 6                    | 10   | 12     | 14-1/2             | 19-1/16                        | 1                          | 136                      |
| 6            | 6.900            | 16–3/8 x 1  | 6–5/8 x 5                                  | 4–5/8 x 7                    | 12-1/2   | 12     | 17-1/8             | 19-1/16                        | 1                          | 185                      |
| 6            | 7.100            | 16–3/8 x 1  | 6–5/8 x 7                                  | 4–5/8 x 7                    | 12-1/2   | 12     | 17-1/8             | 19-1/16                        | 1                          | 185                      |
| 8            | 9.050            | 20–3/8 x 1-1/4                                    | 6–5/8 x 5                                  | 4–5/8 x 7-1/2                | 15-1/2   | 12–3/8 | 20-1/4             | 19-3/16                        | 1                          | 265                      |
| 8            | 9.300            | 20–3/8 x 1-1/4                                    | 6–5/8 x 5                                  | 4–5/8 x 7-1/2                | 15-1/2   | 12–3/8 | 20-1/4             | 19-3/16                        | 1                          | 265                      |
| 10           | 11.100           | 24–7/16 x 2-1/4                                   | 12–3/4 x 4                                 | _                            | 16–5/8   | 13–1/2 | 22-3/8             | 18-5/8                         | 1                          | 300                      |
| 10           | 11.400           | 24–7/16 x 2-1/4                                   | 12–3/4 x 4                                 | -                            | 16–5/8   | 13–1/2 | 22-3/8             | 18-5/8                         | 1                          | 300                      |
| 12           | 13.200           | 28–7/16 x 2-1/4                                   | 12–7/8 x 4                                 | _                            | 18–3/4   | 13–1/2 | 24-1/2             | 18-5/8                         | 1                          | 335                      |
| 12           | 13.500           | 28–7/16 x 2-1/4                                   | 12–7/8 x 4                                 | —                            | 18–3/4   | 13–1/2 | 24-1/2             | 18-5/8                         | 1                          | 335                      |
| 16           | 17.400           | 32–7/16 x 2-1/4                                   | 14–7/8 x 4                                 | _                            | 24   | 16     | 30                 | 21-1/8                         | 2                          | 554                      |
| 16           | 17.800           | 32–7/16 x 2-1/4                                   | 14–7/8 x 4                                 | _                            | 24   | 16     | 30                 | 21-1/8                         | 2                          | 554                      |
| 20           | 21.600           | 40–7/16 x 2-1/4                                   | 14–1 x 4                                   | _                            | 30   | 17     | 36                 | 22-1/8                         | 3                          | 770                      |
| 20           | 22.060           | 40–7/16 x 2-1/4                                   | 14–1 x 4                                   | _                            | 30   | 17     | 36                 | 22-1/8                         | 3                          | 770                      |
| 24           | 25.800           | 48–7/16 x 2-1/4                                   | 14–1 x 4                                   | _                            | 33-7/8   | 18     | 39-7/8             | 23-1/8                         | 3                          | 853                      |
| 24           | 26.320           | 48 –7/16 x 2-1/4                                  | 14– 1 x 4                                  | -                            | 33-7/8   | 18     | 39-7/8             | 23-1/8                         | 3                          | 853                      |

Dimensions are in inches unless otherwise noted.

<sup>1</sup> End Screws are high-grade steel, and have square heads, 3/8" across flats.

<sup>2</sup> Side Bolts are high-grade steel with trackheads and rolled threads through 8" size. Larger sizes are supplied with galvanized machine bolts.

<sup>3</sup> Vent supplied with ASME B1.20.1 pipe threads.

<sup>4</sup> Fabricated Style 126 sleeves have end seal design similar to Style 96.

# **Style 110 Weld-On Reinforcing Sleeves**

#### Split repair and integrity reinforcement sleeve for repair of welded joints

Pipeline engineers assure the safety of field joints by installing Dresser Style 110 reinforcing sleeves on welded joints where special precautions are required. Style 110 sleeves can used on defective 'trouble spots' on piping systems, at highway, river and railroad crossings, at overbends, at tie-ins, in marshy ground, near buildings, and other places where special precautions are necessary.

The Style 110 sleeve lends itself to field welding without preheating, using ordinary field welding procedures. All sleeves are factory prepared with standard welding bevel, machine flame cut for uniformity and ease of welding, and come with a drilled vent hole to preclude pressure buildup between sleeve and pipe.

Built to rigid Dresser specifications, Style 110 sleeves have a minimum yield strength of 50,000 psi and an ultimate strength of 70,000 psi. Style 110 sleeves are supplied in all standard sizes, lengths and thicknesses (see charts below). Custom-built larger sizes and lengths available upon request.





#### Style 110 Sleeves - Dimension specifications for nominal sizes 4" thru 30" and lengths 6" - 24" (with vent)

| Nom.<br>Size<br>(in) | ID Diam.<br>'A'<br>Pipe OD<br>(in) | Diam.<br>'B'<br>(in) | Length<br>'L'<br>(in)                          | Thickness<br>'T'<br>(in)   | Approx.<br>Ship Wt.<br>(lbs)                        | Nom.<br>Size<br>(in) | ID Diam.<br>'A'<br>Pipe OD<br>(in) | Diam.<br>'B'<br>(in) | Length<br>'L'<br>(in)                                | Thickness<br>'T'<br>(in)  | Approx.<br>Ship Wt.<br>(lbs)                                    |
|----------------------|------------------------------------|----------------------|--|--|---|----------------------|------------------------------------|----------------------|--|---|---|
| 4                    | 4-1/2                              | 5-3/8                | 4  | 5/16   | 5.5   | 20                   | 20                                 | 21-1/2               | 6  | 1/2   | 58  |
| 6                    | 6-5/8                              | 7-1/2                | 6  | 3/8  | 16  |                      |                                    |                      | 9  | 1/2   | 86  |
| 8                    | 8-5/8                              | 9-1/2                | 6  | 3/8  | 19  |                      |                                    |                      | 20   | 1/2   | 112   |
| 8                    | 5/8                                | 9-1/2                | 8  | 3/8  | 27  |                      |                                    |                      | 21   | 1/2   | 195   |
| 8                    | 8-5/8                              | 9-1/2                | 6  | 1/2  | 26  | 22                   | 22                                 | 23-1/3               | 6  | 3/8   | 47  |
| 8                    | 8-5/8                              | 9-1/2                | 8  | 1/2  | 35  |                      |                                    |                      | 9  | 3/8   | 70  |
| 10                   | 10-3/4                             | 11-5/8               | 6  | 3/8  | 23  |                      |                                    |                      | 12   | 3/8   | 92<br>166   |
| 10                   | 10-3/4                             | 11-5/8               | 10   | 3/8  | 38  |                      |                                    |                      | 6  | 1/2   | 64  |
| 10                   | 10-3/4                             | 11-5/8               | 6  | 1/2  | 31  |                      |                                    |                      | 9  | 1/2   | 94  |
| 10                   | 10-3/4                             | 1/1-5/8              | 10   | 1/2  | 5U<br>07  |                      |                                    |                      | 12<br>22   | 1/2<br>1/2  | 123<br>230  |
| 12                   | 12-3/4                             | 14-1/4               | 9<br>12<br>6<br>9<br>12                        | 3/8<br>3/8<br>1/2<br>1/2<br>1/2                                    | 40<br>45<br>36<br>55<br>74                          | 24                   | 24                                 | 25-1/2               | 6<br>9<br>12<br>16<br>24                             | 3/8<br>3/8<br>3/8<br>3/8<br>3/8<br>3/8                                    | 51<br>76<br>100<br>133<br>198                                   |
| 14                   | 14                                 | 15-1/2               | 6<br>9<br>14<br>6<br>9                         | 3/8<br>3/8<br>3/8<br>1/2<br>1/2                                    | 30<br>45<br>70<br>40<br>60                          |                      |                                    |                      | 6<br>9<br>12<br>16<br>24                             | 1/2<br>1/2<br>1/2<br>1/2<br>1/2   | 69<br>101<br>133<br>177<br>265                                  |
| 16                   | 16                                 | 17-1/2               | 14<br>6<br>9<br>12<br>16<br>6<br>9<br>12<br>16 | 1/2<br>3/8<br>3/8<br>3/8<br>3/8<br>1/2<br>1/2<br>1/2<br>1/2<br>1/2 | 94<br>35<br>52<br>68<br>90<br>46<br>70<br>90<br>120 | 26                   | 26                                 | 27-1/2               | 6<br>9<br>12<br>16<br>26<br>6<br>9<br>12<br>16<br>26 | 3/8<br>3/8<br>3/8<br>3/8<br>1/2<br>1/2<br>1/2<br>1/2<br>1/2<br>1/2<br>1/2 | 56<br>82<br>109<br>143<br>232<br>75<br>110<br>144<br>190<br>310 |
| 18                   | 18                                 | 19-1/2               | 6<br>9<br>12<br>18<br>6<br>9<br>12<br>18       | 3/8<br>3/8<br>3/8<br>3/8<br>1/2<br>1/2<br>1/2<br>1/2<br>1/2        | 39<br>58<br>77<br>114<br>51<br>78<br>101<br>152     | 30                   | 30                                 | 31-1/2               | 6<br>9<br>12<br>16<br>30<br>6<br>9                   | 3/8<br>3/8<br>3/8<br>3/8<br>3/8<br>3/8<br>1/2<br>1/2                      | 64<br>95<br>125<br>164<br>310<br>85<br>127                      |
| 20                   | 20                                 | 21-1/2               | 6<br>9<br>12<br>20                             | 3/8<br>3/8<br>3/8<br>3/8   | 43<br>64<br>84<br>139                               |                      |                                    |                      | 12<br>16<br>30                                       | 1/2<br>1/2<br>1/2   | 166<br>220<br>410   |

Dimensions are in inches unless otherwise noted.

NOTE: Larger diameters, higher pressure and metric sizes may be furnished upon request. Please consult factory.

## Style 110 Repair & Reinforcing Sleeves

Style 110 Sleeves - (Maximum Operating Pressure by Location)

| Pipe Size (OD) x Wall<br>Thickness | Class 1 | Class 2 | Class 3 | Class 4 |
|------------------------------------|---------|---------|---------|---------|
| 4-1/2" OD x 5/16" Wall             | 3130 G  | 2605 G  | 2170 G  | 1735 G  |
| 6-5/8" OD x 3/8" Wall              | 2615 G  | 2180 G  | 1815 G  | 1450 G  |
| 8-5/8" OD x 3/8" Wall              | 2105 G  | 1755 G  | 1460 G  | 1170 G  |
| 8-5/8" OD x 1/2" Wall              | 2704 G  | 2285 G  | 1900 G  | 1520 G  |
| 10-3/4" OD x 3/8" Wall             | 1745 G  | 1450 G  | 1210 G  | 965 G   |
| 10-3/4" OD x 1/2" Wall             | 2280 G  | 1900 G  | 1580 G  | 1265 G  |
| 12-3/4" OD x 3/8" Wall             | 1440 G  | 1200 G  | 1000 G  | 800 G   |
| 12-3/4" OD x 1/2" Wall             | 1885 G  | 1570 G  | 1310 G  | 1045 G  |
| 14" OD x 3/8" Wall                 | 1325 G  | 1105 G  | 920 G   | 735 G   |
| 14" OD x 1/2" Wall                 | 1745 G  | 1450 G  | 1210 G  | 965 G   |
| 16" OD x 3/8" Wall                 | 1180 G  | 985 G   | 820 G   | 655 G   |
| 16" OD x 1/2" Wall                 | 1555 G  | 1295 G  | 1080 G  | 860 G   |
| 18" OD x 3/8" Wall                 | 1065 G  | 885 G   | 740 G   | 590 G   |
| 18" OD x 1/2" Wall                 | 1400 G  | 1170 G  | 975 G   | 780 G   |
| 20" OD x 3/8" Wall                 | 970 G   | 805 G   | 670 G   | 535 G   |
| 20" OD x 1/2" Wall                 | 1275 G  | 1065 G  | 885 G   | 710 G   |
| 22" OD x 3/8" Wall                 | 890 G   | 740 G   | 615 G   | 490 G   |
| 22" OD x 1/2" Wall                 | 1175 G  | 975 G   | 815 G   | 650 G   |
| 24" OD x 3/8" Wall                 | 820 G   | 685 G   | 570 G   | 455 G   |
| 24" OD x 1/2" Wall                 | 1085 G  | 905 G   | 750 G   | 600 G   |
| 26" OD x 3/8" Wall                 | 760 G   | 635 G   | 530 G   | 420 G   |
| 26" OD x 1/2" Wall                 | 1010 G  | 840 G   | 700 G   | 560 G   |
| 30" OD x 3/8" Wall                 | 665 G   | 555 G   | 465 G   | 370 G   |

| Material Specifications  |                    |  |  |  |  |  |  |
|--|--------------------|--|--|--|--|--|--|
| Body High strength, low carbon<br>steel meeting ASTM A572<br>GR 50 |                    |  |  |  |  |  |  |
| Style 110 Ratings  |                    |  |  |  |  |  |  |
| Yield Strength   | 50,000 psi minimum |  |  |  |  |  |  |
| Temperature<br>Ratings   | -20° F to +150°    |  |  |  |  |  |  |

Dimensions are in inches unless otherwise noted.

NOTE: Style 110 sleeve design pressure for class location has been determined using the formula shown in DOT Regulation 192, Section 192.105, assuming an 80% joint factor for the longitudinal field weld.

For Oil Applications Refer to Class 1 Ratings as per DOT Regulation 195.

### Style 115 Reinforcing Sleeves

Where special precautions are needed, you can strengthen field joints by installing Style 115 reinforcing sleeves. The Style 115 is a full-wrap split sleeve and can be manufactured to any length

required. Style 115 sleeves are factory-prepared with standard welding bevel and are machine flame-cut for uniformity and ease of installation.





Style 115 Full-Wrap Split Sleeves are custom-fabricated to exact customer specifications. Please consult factory for details on your particular application requirements.

# **Style 220 Repair & Reinforcing Sleeves**

#### For permanent reinforcement of defective coupled joints

Similar in design to the Style 110, Dresser Style 220 weld-on sleeves encompass a "pumpkin" sleeve design and are commonly used to repair corrosion pits and stress cracks. In addition, these sleeves offer a permanent repair over leaking coupled joints, flanges, valves or screw collars. Style 220 sleeves also provide a means of ensuring safety against pipe-end pullout when used to reinforce pipelines on high-pressure piping systems.

The steel construction properties of the Style 220 sleeve lends itself to field welding without preheating, using ordinary field welding procedures. All sleeves are factory prepared with standard welding bevel, machine-flame cut for uniformity and ease of welding, and come with a drilled vent hole to preclude pressure build-up between sleeve and pipe.

Built to rigid Dresser specifications, Style 220 sleeves have a minimum yield strength of 50,000 psi and an ultimate strength of 70,000 psi. Style 220 sleeves are supplied in all sizes, lengths and thicknesses as shown in chart below. Larger sizes can be supplied with weld-on handles for ease of installation.





#### Style 220 Sleeves - Dimension specifications for sizes 2"- 26"

| Nom.<br>Size<br>(in) | ID<br>Diam. 'A'<br>Pipe OD<br>(in) | Inside<br>Diam.<br>'B' | Inside<br>Length<br>'L' | Outlet<br>Dimen.<br>'N' | Overall<br>Length<br>"M" | Thickness<br>"T" | Approx.<br>Ship Wt.<br>(lbs) |
|----------------------|------------------------------------|------------------------|-------------------------|-------------------------|--------------------------|------------------|------------------------------|
| 2*                   | 2-3/8                              | 8-3/8                  | 10-1/2                  | 1-1/4                   | 23-1/4                   | 5/16             | 45                           |
| 3*                   | 3-1/2                              | 9-1/2                  | 10-1/2                  | 1-1/4                   | 23-1/4                   | 5/16             | 49                           |
| 4                    | 4-1/2                              | 10-1/2                 | 10                      | 2                       | 20-1/4                   | 5/16             | 54                           |
| 6                    | 6-5/8                              | 12-5/8                 | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 96                           |
| 8                    | 8-5/8                              | 14-5/8                 | 13-1/3                  | 1-3/8                   | 21-3/4                   | 3/8              | 112                          |
| 10                   | 10-3/4                             | 16-3/4                 | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 128                          |
| 10                   | 10-3/4                             | 16-3/4                 | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 175                          |
| 12                   | 12-3/4                             | 18-3/4                 | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 150                          |
| 12                   | 12-3/4                             | 18-3/4                 | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 198                          |
| 14                   | 14                                 | 20                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 160                          |
| 14                   | 14                                 | 20                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 215                          |
| 16                   | 16                                 | 22                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 176                          |
| 16                   | 16                                 | 22                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 240                          |
| 18                   | 18                                 | 24                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 195                          |
| 18                   | 18                                 | 24                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 260                          |
| 20                   | 20                                 | 26                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 216                          |
| 20                   | 20                                 | 26                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 288                          |
| 22                   | 22                                 | 28                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 230                          |
| 22                   | 22                                 | 28                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 307                          |
| 24                   | 24                                 | 30                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 248                          |
| 24                   | 24                                 | 30                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 330                          |
| 26                   | 26                                 | 32                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 3/8              | 315                          |
| 26                   | 26                                 | 32                     | 13-1/2                  | 1-3/8                   | 21-3/4                   | 1/2              | 350                          |

**Material Specifications** 

Body High strength, low carbon steel meeting ASTM A572 GR 50 / ASTM A588

Dimensions are in inches unless otherwise noted.

NOTE: Larger diameters available upon request.

Please consult factory with your particular application requirements.

\* 2" and 3" sizes have minimum yield strength of 35,000 psi.

# **Style 220 Repair & Reinforcing Sleeves**

Style 220 Sleeves - (Maximum Operating Pressure by Location)

| Pipe Size (OD) x Wall<br>Thickness (in) | Class 1 | Class 2 | Class 3 | Class 4 |
|---|---------|---------|---------|---------|
| 2-3/8 x 5/16 Wall                       | 1200 G  | 1000 G  | 825 G   | 650 G   |
| 3-1/2 x 5/16 Wall                       | 1000 G  | 875 G   | 725 G   | 575 G   |
| 4-1/2 x 5/16 Wall                       | 1615 G  | 1345 G  | 1120 G  | 895 G   |
| 6-5/8 x 3/8 Wall                        | 1610 G  | 1345 G  | 1120 G  | 895 G   |
| 8-5/8 x 3/8 Wall                        | 1400 G  | 1170 G  | 975 G   | 780 G   |
| 10-3/4 x 1/4 Wall                       | 830 G   | 695 G   | 580 G   | 460 G   |
| 10-3/4 x 3/8 Wall                       | 1230 G  | 1025 G  | 855 G   | 685 G   |
| 10-3/4 x 1/2 Wall                       | 1620 G  | 1350 G  | 1125 G  | 900 G   |
| 12-3/4 x 3/8 Wall                       | 1105 G  | 920 G   | 765 G   | 615 G   |
| 12-3/4 x 1/2 Wall                       | 1455 G  | 1215 G  | 1010 G  | 810 G   |
| 14 x 3/8 Wall                           | 1040 G  | 865 G   | 720 G   | 575 G   |
| 14 x 1/2 Wall                           | 1370 G  | 1140 G  | 950 G   | 760 G   |
| 16 x 3/8 Wall                           | 945 G   | 790 G   | 655 G   | 525 G   |
| 16 x 1/2 Wall                           | 1250 G  | 1040 G  | 870 G   | 695 G   |
| 18" x 3/8 Wall                          | 870 G   | 725 G   | 605 G   | 480 G   |
| 18 x 1/2 Wall                           | 1150 G  | 960 G   | 800 G   | 640 G   |
| 20 x 3/8 Wall                           | 805 G   | 670 G   | 560 G   | 445 G   |
| 20 x 1/2 Wall                           | 1065 G  | 885 G   | 740 G   | 590 G   |
| 22 x 3/8 Wall                           | 750 G   | 625 G   | 520 G   | 415 G   |
| 22 x 1/2 Wall                           | 990 G   | 825 G   | 690 G   | 550 G   |
| 24 x 3/8 Wall                           | 700 G   | 585 G   | 485 G   | 390 G   |
| 24 x 1/2 Wall                           | 925 G   | 770 G   | 645 G   | 515 G   |
| 26 x 3/8 Wall                           | 655 G   | 545 G   | 455 G   | 365 G   |
| 26 x 1/2 Wall                           | 870 G   | 725 G   | 605 G   | 480 G   |

| Style 220 Ratings      |                    |  |  |  |  |
|------------------------|--------------------|--|--|--|--|
| Yield Strength         | 50,000 psi minimum |  |  |  |  |
| Temperature<br>Ratings | -20° F to +150°    |  |  |  |  |



All dimensions are in inches unless otherwise noted.

### **Style 220-S Reinforcing Sleeves**

#### For smaller diameter repair from 3/4" to 2" ID

The Dresser Style 220-S reinforcing sleeve is a weld-over sleeve for reinforcing threaded collars, welded joints or compression couplings on small diameter pipe from 3/4" ID through 2" ID sizes. The sleeves are made to rigid Dresser specifications meeting ASTM-A513, GR1015 specs, and have a yield strength of 35,000 psi, and an ultimate strength of 48,000 psi.

Style 220-S sleeves are furnished in matched halves and all longitudinal edges are factory beveled for welding. A drilled vent hole precludes pressure build-up between sleeve and pipe during welding. Style 220-S sleeves are rated at 350 psi working pressure and meet the requirements applicable to DOT #192 codes.



| Pipe Size<br>(OD) | Nominal<br>Size | Diameter<br>(A) |
|-------------------|-----------------|-----------------|
| 1.050             | 3/4"            | 1-1/8"          |
| 1.315             | 1"              | 1-3/8"          |
| 1.660             | 1-1/4"          | 1-3/4"          |
| 1.990             | 1-1/2"          | 2"              |
| 2.375             | 2"              | 2-7/16"         |

### **Dresser Product Coatings**

#### **ALCLAD<sup>™</sup> Epoxy Coating**

Dresser Epoxy is a thermoset, fusion-bonded, grey coating and has outstanding physical properties and can be utilized in many piping system applications due to such features as:

- · High coating dielectric strength.
- Excellent disbondment resistance in cathodically protected systems.
- · Resistant to soil stress and fungi.
- Excellent adhesion in an oven-cured factory application.

All constituents of the epoxy cured film are FDA approved for exposure to fluids for human consumption. ALCLAD also provides an excellent coating for use on components of cathodic protected distribution systems. Thermoset epoxy coatings meet DOT and Federal regulation 192.461. Please consult the factory for special line content applications.

#### **Dresser RED-D Shopcoat**

Dresser Shopcoat paint is a waterborne finish, pigmented with red oxide. RED-D provides a suitable base over which primers and final coatings can be applied.

Dresser shopcoat provides a smooth, clean, non-greasy, non-sticky surface and protects all products from corrosion in normal storage situations. It is compatible with primer and enamel coatings of either hard or soft grades of plasticized or unplasticized coal tar enamels, and with asphalt coatings.

For above ground, Dresser Shopcoat will take most of the usual types of paint, including paints with color added, without bleeding through.

### **Applicable Warnings for Dresser Repair Products**

#### **Split Sleeves**



When pipe pullout could occur, pipe joint MUST be anchored. Failure to anchor pipe joint could result in escaping gas that could ignite and cause property damage, serious injury or death.



When pipe pullout could occur, pipe joint MUST be anchored. Failure to anchor pipe joint could result in escaping line content that could ignite and cause property damage, serious injury or death.

NOTE: Always read the product installation instructions before installing any Dresser products.

#### Visit us at: www.dresserutility.com

Dresser Utility Solutions reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Dresser sales representative for the most current information.

**Dresser Pipeline Solutions** 41 Fisher Avenue Bradford, PA 16701 T: 814.362.9300 F: 814.362.9344



© 2021 Natural Gas Solutions North America, LLC - All rights reserved. The Dresser Logo and all Trademarks containing the term "Dresser" are the property of Dresser, LLC, a subsidiary of Baker Hughes