

# Meter Comparison Guide

## 10C25, D1000, D800 Dresser Meters

	Units	10C25	D1000	D800
Base Rating	acfh	1000	1000 1700	800 1700
Maximum Allowable Pressure (MAOP)	psig	25	25	25
Rangeability +/-1%	ratio	125:1 (at 1000acfh)	125:1 (at 1000acfh)	100:1 (at 800acfh)
Rangeability +/-2%	ratio	200:1 (at 1000acfh)	200:1 (at 1000acfh)	160:1 (at 800acfh)
Start Rate	cfh	0.30	0.30	0.30
Stop Rate	cfh	0.15	0.15	0.15
Maximum Operating Speed	rpm	3825	3825	3825
Testing Compatibility		Dresser Model 5 Dresser Model 6 SNAP	Dresser Model 5 Dresser Model 6 SNAP	Dresser Model 5 Dresser Model 6 SNAP
Ferrule (Spud) Connection		30 LT/45 LT Sprague #3, #4	30 LT/45 LT Sprague #3, #4, #5 1-1/2" FNPT	30 LT/45 LT Sprague #3, #4, #5 1-1/2" FNPT
Spud to Spud	in.	6.625	11	11
Net Weight	lbs.	13	24	24
Shipping Weight	lbs.	16	28.5	28.5
Carton Size	in.	13 1/4 x 11 x 9 1/4	19 x 12 3/4 x 16	19 x 12 3/4 x 16
Max Units per pallet*	qty.	60	18	18

\*Standard pallet size: 40" x 48"

**Dresser Meters & Instruments**

16240 Port Northwest Drive

Houston, TX 77041

T: 1-800-521-1114

F: 1-800-335-5224

The Dresser Logo and all Trademarks containing the term "Dresser" are the property of Dresser, LLC, a subsidiary of Baker Hughes, a GE Company.



[www.dresserngs.com](http://www.dresserngs.com)

Dresser Meter Comparison Guide NGS.MI.0109  
06.19