

Phone: 716-372-0160

Fax: 716-372-1767

sales@tps.us

www.tps.us

Quick-Cam® RR (Regular Range) Repair Clamp



Nominal Diameter	Lower Diameter	Upper Diameter	CTS	IPS	DIP	Pit Cast	AC100	AC150	AC200
2	2.35	2.65	2.63	2.38		2.50			
2-1/2	2.70	3.00		2.88					
3	3.46	3.70		3.50					
4	4.75	5.14	5.13		4.80	5.00			
6	6.84	7.24			6.90	7.10			
6 o.s.	7.05	7.45				7.10	7.40	7.37	7.32
8	8.99	9.39		8.63	9.05	9.30			
8 o.s.	9.27	9.67				9.30	9.57	9.62	9.50
10	11.04	11.44			11.10	11.40			
12 u.s.	12.62	13.02		12.75					
12	13.10	13.50			13.20	13.50			
12 o.s.	14.00	14.40		14.00			14.04	14.38	14.38



Technical Details

Quick Cam RR (Regular Range)

Gasketing: NSF 61 Approved SBR Rubber approved for water and sewer service (call for other line content compatibility)

Spanner Plate: Heavy Gauge 18-8 stainless steel

Lug Material: Type 304, 18-8 stainless steel or E-Coated Ductile Iron

Shell Material: Heavy Gauge Type 304, 18-8 stainless steel

Pressure Rating: Up to 150 psi maximum working pressure

Temperature Rating: up to 180 degrees

Available Widths: 7.5, 10, 12, 15, 20, and 24” widths

Nuts, Bolts and Washers: 304 Stainless steel Bolts and Washers with heavy double coated fluoropolymer coatings or coated carbon steel nuts and bolts also available upon request

Testing per AWWA C-230-16 on a full 360-degree beam break

Outlets available in ½ to 2” NPT or CC threads

Note: Pressure, temperature and bolt torque can vary depending upon the product diameter, pipe material and type of connection. **Note:** Always refer to instructions on product label.

Quick-Cam RR is not to be used on HDPE Pipe Material.

Standards: ASTM A380-06, ASTM A967-05, ANSI-AWWA C230-16, NSF-ANSI Standard 61, ASTM D2000-12, ASTM A351, ASTM A536

Call factory for sizes not shown on chart

Caution: Repair Clamps must not be re-used until refurbished with new bolts and gaskets at the TPS factory